

[54] **RETRACTOR FOR PERMEATOR OR FILTER MODULE**

[75] Inventor: **Joseph C. Holzer, Liverpool, N.Y.**

[73] Assignee: **Eastman Kodak Company, Rochester, N.Y.**

[21] Appl. No.: **117,409**

[22] Filed: **Nov. 2, 1987**

Related U.S. Application Data

[63] Continuation of Ser. No. 902,735, Sep. 2, 1986, abandoned.

[51] Int. Cl.⁴ **B01D 13/00**

[52] U.S. Cl. **210/238; 210/321.83; 210/494.1**

[58] Field of Search **210/232, 238, 321.83, 210/450, 494.1**

[56] **References Cited**

U.S. PATENT DOCUMENTS

2,642,187	6/1953	Bell	210/169
2,731,155	1/1956	James	210/169
2,822,201	2/1958	Wood	210/238 X
3,189,179	6/1965	McMichael	210/238
3,504,796	4/1970	Bray	210/137

3,542,203	11/1970	Hancock et al.	210/321
3,568,843	3/1971	Brown	210/321
3,883,430	5/1975	Codo	210/238 X
4,016,083	4/1977	Sakaguchi et al.	210/433.2
4,110,219	8/1978	Maples	210/245
4,301,013	11/1981	Setti	210/637

FOREIGN PATENT DOCUMENTS

947841	8/1956	Fed. Rep. of Germany
1932585	1/1971	Fed. Rep. of Germany
2004472	4/1979	United Kingdom

Primary Examiner—Frank Spear
Attorney, Agent, or Firm—Herman J. Strnisha

[57] **ABSTRACT**

A retractor handle is attached to the retraction end of a core wound permeator or filter module for withdrawing the module from its containment housing without requiring special tools. The retraction handle can be a resin pull ring flexibly attached to a flange of a plug that closes the retraction end of the core of the permeator or filter module. The retraction handle can also be a wire pull ring having ends seated in sockets formed in a plugged end region of the core.

6 Claims, 4 Drawing Sheets

